



Medium

BERLIN 02

Classic uniform shoe for professionals

The BERLIN is a classic shoe offering SR slip resistance, a breathable leather upper, and SJ Foam for optimum shock absorption. Perfect for catering, food & beverages, and industrial sectors.

| | |
|---------------|---|
| Upper | Nappa Leather |
| Lining | Microsuede |
| Footbed | SJ foam footbed |
| Outsole | PU/Rubber (NBR) |
| Category | O2 / SRC |
| Size range | EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315 |
| Sample weight | 0.445 kg |
| Norms | ASTM F2892:2018 EN ISO 20347:2012 |



BLK



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

Industries:

Catering, Food & beverages, Industry

Environments:

Wet environment, Extreme slippery surfaces, Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|---|-----------------------|-------------|--------------|
| Upper | Nappa Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 3.7 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 34 | ≥ 15 |
| Lining | Microsuede | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 4.7 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 46 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU/Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 72.2 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.53 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.51 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.24 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.27 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 134 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 40.1 | ≥ 20 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.