



Medium

## BESTBOY259 S3

All Bestboy2 features with wool lining & BASF PU/rubber outsole

The Safety Jogger BESTBOY259 safety shoes are perfect for high-risk industries. With features like SR slip resistance, a heat-resistant outsole, cold insulation, and water-resistant upper, they provide unparalleled safety. Enjoy less sweaty feet and body posture pain relief.

Upper	Barton Action Leather
Lining	Fur
Footbed	Fur
Midsole	Steel
Outsole	PU/Rubber (NBR)
Toecap	Steel
Category	S3 / SRC, CI, HRO
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.721 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BLK



**Warm lining**  
Keeps your feet warm and dry in cold environments.

**S3**  
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.

**SRC slip resistance**  
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

**Heat resistant outsole (HRO)**  
The outsole resists high temperatures up to 300°C.

**Cold insulated (CI)**  
Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.

**Water resistant Upper (WRU)**  
Prevents penetration of water if not permanently exposed to high levels.

**Industries:**

Chemical, Cleaning, Construction, Logistics, Mining, Oil &amp; Gas

**Environments:**

Cold environment, Snowy and icy, Warm surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Barton Action Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	2.2	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	25.0	≥ 15
<b>Lining</b>	<b>Fur</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	7.7	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	65.6	≥ 20
<b>Footbed</b>	<b>Fur</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>PU/Rubber (NBR)</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	100	≤ 150
	Outsole slip resistance SRA: heel	friction	0.38	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.40	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	85.7	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	37	≥ 20
<b>Toecap</b>	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	18.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.