



Medium

BESTRUN2 S3

All features of the original Bestrun in an updated design

The Safety Jogger BESTRUN2 safety shoes offer all the features of the original BESTRUN in an updated design: they feature SR slip resistance, a steel toecap and midsole, orthopedic support, and breathable leather upper. Ideal for diverse industries and environments.

| | |
|---------------|---|
| Upper | Barton Action Leather |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Midsole | Steel |
| Outsole | PU/PU |
| Toecap | Steel |
| Category | S3 / SRC |
| Size range | EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310 |
| Sample weight | 0.625 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2011 |



217



DGVU BGR 191
These shoes are suitable for orthopedic insoles and orthopedic alterations. Certified according to BGR 191.




SJ Flex
Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.



Steel toecap
Robust metal support to protect the feet of the wearer against falling or rolling objects.



Steel midsole
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:

Automotive, Catering, Chemical, Cleaning, Construction, Food & beverages, Logistics, Oil & Gas, Industry

Environments:

Dry environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Barton Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 2.2 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 25.0 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 67.6 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 541 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU/PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 68.5 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.36 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.38 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.13 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.18 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 129.3 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 18.5 | ≥ 20 |
| Toecap | Steel | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 20.5 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 18.5 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.