



Medium

X0500 S2

Safety shoe, designed for the food industry

The Safety Jogger X0500 is a low-cut safety shoe ideal for various industries, offering superior protection and comfort. It combines water and oil resistance, heel energy absorption, and a steel toecap for ultimate safety.

| | |
|---------------|---|
| Upper | Nappa Action Leather |
| Lining | Cambrella |
| Footbed | SJ foam footbed |
| Midsole | N/A |
| Outsole | PU/PU |
| Toecap | Steel |
| Category | S2 / SRC |
| Size range | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.525 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2011 |



067



Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Water resistant Upper (WRU)

Prevents penetration of water if not permanently exposed to high levels.



Oil & fuel resistant

The outsole is resistant against oil and fuel.



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



HACCP

HACCP is a testing system based on analysis (identification, evaluation and elimination) of significant health risks, associated with foods, that can lead to disease of consumers. The specially for the food industry developed and HACCP equitable models are made from washable materials.

Industries:

Catering, Chemical, Cleaning, Food & beverages, Medical, Industry

Environments:

Dry environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Nappa Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 2.03 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 21 | ≥ 15 |
| Lining | Cambrella | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 18.27 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 147 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU/PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 46 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.35 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.35 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.14 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.18 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 66.7 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 29 | ≥ 20 |
| Toecap | Steel | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 16 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 18 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.