



Medium

X1100N S3

Mid-cut leather safety shoe for protection in style

The Safety Jogger X1100N is a lightweight, metal-free safety shoe with superior foot protection. It's oil, fuel and slip resistant, offering comfort, flexibility and safety in challenging work environments.

| | |
|---------------|---|
| Upper | Nappa Action Leather |
| Lining | Cambrella |
| Footbed | SJ foam footbed |
| Midsole | Anti-puncture Textile |
| Outsole | PU/PU |
| Toecap | Composite |
| Category | S3 / SRC |
| Size range | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310 |
| Sample weight | 0.676 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2011 |




BLK



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



SJ Flex
Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.



Composite toecap
Metalfree and lightweight, no thermal or electrical conductivity



Oil & fuel resistant
The outsole is resistant against oil and fuel.

Industries:

Automotive, Cleaning, Construction, Logistics, Mining, Oil & Gas, Industry, Uniform

Environments:

Dry environment, Muddy environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Nappa Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 1.8 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 19 | ≥ 15 |
| Lining | Cambrella | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 39.2 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 314.3 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU/PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 110 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.36 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.33 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.14 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.19 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 265 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 24 | ≥ 20 |
| Toecap | Composite | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 14.5 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 22 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.